

LED-Feuchtraumleuchte MISTRALxtreme 1500mm 60W 5000K IP66

Order number: 3109-150120-B-Ware

<?xml:namespace prefix="o" />

- + Gehäuse komplett aus Aluminium und Glas, dadurch extrem witterungsbeständig und für den Außenbereich geeignet
- + Werkseitige 5-polige Durchverdrahtung ermöglicht eine schnelle Montage
- + Mikroprismatisches ESG-Glas für blendfreie Lichtverteilung (UGR < 19)
- + Montagezubehör mitgeliefert (Decken-/Wand- oder abgehängte Montage)
- + Montageklammern sind an der Leuchte frei positionierbar – vorhandene Befestigungspunkte an Decke und Wand können weiter genutzt werden
- + Metall-Kabelverschraubung und Metall-Abdeckung beiliegend
- + Schlagfestigkeit IK08
- + Geeignet für Zentralbatterie

Power consumption in watts: 60; Consumption (kWh/1000h): 60; Net luminous flux in lumens: 7800; Beam angle: 120°; protection class (IP): IP66; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 5000; Power supply: Integrated; Color-rendering-index: CRI > 82; IK protection: IK08; Suited for emergency lighting: yes; Emergency lighting integrated: -; Fire protection "D": yes; Glare-free: UGR < 19; Suitable for through-wiring: Yes; Switch cycles: > 80.000; Cover material: Safety-glass; Input voltage span: 220-240 V AC; Warranty in years: 0; Housing material: Aluminium; Suited for emergency power: -; Input voltage range luminaire: 220-240 V AC; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK08; Suitable for emergency lighting: Yes; Emergency power supply integrated: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Optics of the cover: satin
width: 112mm