

DOTLUX Driver not dimmable 3W Suitable only for Art.No.: 2775

Order number: 2995

- Glare-free luminaire design especially for hotels and restaurants
- Driver and module individually replaceable with lockable quick-connect system
- Maintenance-friendly, modular system components
- Natural color perception thanks to extra high CRI value > 92

Power consumption in watts: 3; protection class (IP): IP20; Input voltage: 176 - 240 V AC/DC; Output current in A: 0,08; Inrush current in A: 0; Protection class: II; Suited for emergency lighting: yes; Output voltage: 32 DC; Input voltage span: 180-250 V AC; Warranty in years: 3; Suited for emergency power: -; Input voltage range luminaire: 180-250 V AC; ETIM Gruppen-ID: EC002710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: Yes; Suited for emergency lighting: Yes; Model: -; Suited for outdoor use: No; Housing: Plastic housing; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany
width: 38mm