

DOTLUX Indoor wall light FLAME 8W 3000K white

Order number: 5997-030110

- Modern, decorative wall light with direct and indirect lighting
- Unique design with great decorative effect
- Excellent heat management thanks to aluminum housing ensures a long service life

Power consumption in watts: 8; Net luminous flux in lumens: 632; Lumen per watt: 79; Beam angle: 110°; protection class (IP): IP20; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 80; Power Factor: 0,88; Inrush current in A: 0; IK protection: IK00; Lumen per watt: 79; Protection class: I; Voltage type: AC; Housing colour: white; Suited for emergency lighting: No; Warranty in years: 3; L80/B10: 54000; similar to RAL-Colour: 9006; Suitable for surface mounting: Yes; Suitable for mounting: No; Energy efficiency class according to EU regulation 2019/2015: not required; Mounting location: Indoor; Lifetime L80/B10 at 25°C: 54000; LED-Lifetime light source L70/B50 at 25°C: 81000; ETIM Gruppen-ID: EC002892; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: No; Suitable for light line configuration: No; Suitable for workplace according to EN 12464-1: No; Material cover: Plastic matt/satinized; With control gear: No; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: Yes; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: Yes; Dimming phase cut-off: Yes; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Impact strength: IK00; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: No; Covering of the luminaire with thermally insulating material possible: No; With air slots: No; Filament test according to IEC 60695-2-11: 750 °C - 30 s; Type of wiring: Ending; Luminous flux adjustable: Positions; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Exchangeable control gear: No; Suitable for lamp power in w: 8; Lamp type: LED not exchangeable; Emergency power supply integrated: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 81000; Lifetime L90/B10 at 25°C: 27000; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: F; Light sharing: Asymmetric; Colour of light adjustable: No; Beam angle adjustable: No; Type of grid: Matt; Light outlet: Direct/indirect; Surface protection housing: Plastic-coated; Light distributor: Other; Beam angle: Extreme wide beam >80°; Connection type: Other
width: 140mm