

DOTLUX LED Anbauleuchte QUADGUARDdali 650x650mm 200W 4000K DALI B-Ware

Order number: 4736-040120-B-Ware

- Particularly easy on the eyes due to 9 times larger illuminated surface than conventional hall floodlights, therefore also ideal for ball sports.
- Extremely uniform illumination due to diffuse light, glare limitation UGR typically <23
- Ball impact certified, solid housing with satinised toughened safety glass cover "ULTRA CLEAR SATINATO
- Certified for various mounting methods (Fix mounting bracket, suspension lugs)
- Fatigue-free, flicker-free light guarantees high-quality HD video recordings
- Pre-mounted Stucchi quick connector (connection socket included)
- The pressure equalisation valve increases the service life of the seals and prevents condensation in the luminaire
- Suitable for central battery (also available as single battery version)
- Sustainable, repairable product design MADE IN EUROPE
- Silicone-free construction for sensitive production areas
- DALI dimmable version

Net luminous flux in lumens: 24500; Lumen per watt: 123; Power consumption in watts: 200; Beam angle: 120°; protection class (IP): IP65; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,98; Inrush current in A: 0; IK protection: IK10; Lumen per watt: 123; Protection class: I; Housing colour: white; Ballproof: yes; Warranty in years: 0; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO02892; Impact strength: IK10; Dimming DALI-2: Yes; Pulse duration in µs: 0