

DOTLUX LED-Aufbauleuchte PANELbig 400x400mm 32W COLORselect B-Ware

Order number: 4468-0FW120-B-Ware

- Eine Artikelnummer - drei Lichtfarben durch COLORselect einstellbar
- Noch schnellere Montage durch speziell entwickelte Grundplatte mit vormontiertem Netzteil
- Massives, pulverbeschichtetes Metallgehäuse
- Größere Lichtfläche durch dünneren Rahmen
- Ermüdungsfreies Arbeiten durch flimmerfreies Licht
- Anschluss über Schnellanschlussklemme
- Geeignet für HCL (HCL-Netzteil und Steuerung notwendig)

Net luminous flux in lumens: max. 2500; Power consumption in watts: max. 32; Consumption (kWh/1000h): max. 32; Lumen per watt: 78; Beam angle: 120°; protection class (IP): IP40; Light color: multicoloured; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Power supply: Separate, enclosed; Color-rendering-index: CRI > 92; Power Factor: 0,95; Special feature: Flicker-free; Lumen per watt: 78; Protection class: II; Voltage type: AC; Housing colour: white; Switch cycles: > 100.000; Food-Ready: Yes; Input voltage span: 220-240 V AC; Warranty in years: 0; Housing material: Aluminium; L/B value: L80/B10; Input voltage range luminaire: 220-240 V AC; Assortment: Highline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Optics of the cover: frosted; Cord length: 30 cm