

DOTLUX LED Battery Spotlight WORKERmini 20W 6500K 7.4V

Order number: 3666-060120

- Adjustable, glare-free light surfaces for homogeneous illumination with snap-in function
- Extremely compact, impact-resistant (IK08) and splash-proof (IP65) plastic housing
- Ergonomic carrying handle with integrated metal tripod mount
- Dimmable in three brightness levels with battery charge indicator
 - 30% light output = 9 hours
 - 50% light output = 6 hours
 - 100% light output = 3 hours
(charging time max. 5 hours)
- Incl. charging cable for car/truck 12/24V and 220 V
- Inexpensive, replaceable, integrated lithium-ion battery
- Continuous operation via 220 V charging cable at full brightness level possible

Power consumption in watts: 20; Net luminous flux in lumens: 1900; Lumen per watt: 95; Beam angle: 120°; protection class (IP): IP65; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 40.000 h at 25°C; Color temperature in Kelvin: 6500; Color-rendering-index: CRI > 82; Inrush current in A: 0; IK protection: IK07; Lumen per watt: 95; Protection class: III; Housing colour: multicoloured; Switch cycles: > 80.000; Warranty in years: 3; Dimming without dimmer: No; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO01744; Impact strength: IK07; Suitable for lamp power in w: 18; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: E width: 180mm