

**DOTLUX LED-Downlight CIRCLEmini 2700K 6,5W Housing: high-grade steel - very low installation depth - (B-Stock)**

Order number: 2786-227038-B-Ware

- Perfect for renovations due to low installation depth and large coverage
- Driver and module individually replaceable with lockable quick plug-in connection
- Maintenance-friendly, modular system components
- Natural colour perception thanks to the extra high CRI value > 92
- This luminaire can be extended for use as emergency lighting.  
(The battery kit is required)

ATTENTION: Dust inclusions and slight scratches on the paintwork. Technically flawless.

Power consumption in watts: 6,5; Consumption (kWh/1000h): 6,5; Net luminous flux in lumens: max. 550; Beam angle: 38°; protection class (IP): IP20; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 2700; Power supply: Separate order; Color-rendering-index: CRI > 92; Inrush current in A: 0; Switch cycles: > 100.000; Installation opening diameter in mm: 68-88; Warranty in years: 0; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC001744; Dimming depending on control gear: Yes; Pulse duration in µs: 0; Dreh- /Schwenkbar: swivelling +/-30°; Adjustability: Swivelling  
diameter: 94mm