

DOTLUX LED-Leuchte DISCugr Ø400mm 40W COLORselect und POWERselect DALI

Order number: 900049

- Flexible use as desired: available as ceiling, wall, surface-mounted or pendant luminaire in 3 sizes (400,600,800mm)
- Glare-free working thanks to microprismatic diffuser UGR<19 (suitable for computer workstations)
- Modern powder-coated aluminium housing (black - similar to RAL9005) with stepped luminaire housing 55mm high
- Easy and quick installation via EASYbase platform
- Individually adjustable for a variety of applications thanks to COLORselect technology
- Adjustable output with POWERselect (47W / 55W / 68W / 75W)
- Pleasant feeling of space due to indirect light component
- Sustainable product design thanks to interchangeable components

Lumen per watt: 105; Power consumption in watts: 35-40; Net luminous flux in lumens: 3500-4300; protection class (IP): IP40; Light color: multicoloured; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/3500/4000; Frequency range in Hz: 50/60; Color-rendering-index: CRI > 82; Lumen per watt: 105; Protection class: I; Housing colour: black; Switch cycles: > 100.000; Input voltage span: 220-240 V AC; similar to RAL-Colour: 9005; Input voltage range luminaire: 220-240 V AC; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Dimming DALI-2: Yes; Dimming phase cut-on: No; Dimming GPRS: No; Light colour according to EN 12464-1: warm white <3300 K