

DOTLUX LED-Lichtbandsystem LINEAcompact 100W breitstrahlend 2886mm 4000K nicht dimmbar B-Ware

Order number: 4944-040160-B-Ware

- New light band concept with 2-length light units for fastest and easiest installation
- All units are delivered fully assembled and only need to be plugged together
- Flexible phase selection directly at the luminaire
- Patent-protected LED cover ensures error-free assembly
- High-quality aluminum core board guarantees perfect cooling and a long service life of the LM80 certified LEDs
- Future-proof with replaceable LED module and separate driver

Consumption (kWh/1000h): 100; Lumen per watt: 167; Power consumption in watts: 100; Net luminous flux in lumens: 16700; Beam angle: 160°; protection class (IP): IP54; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Frequency range in Hz: 50/60; Power supply: Internal; Color-rendering-index: CRI > 82; Power Factor: 0,98; Inrush current in A: 0; Lumen per watt: 167; Protection class: I; Voltage type: AC; Switch cycles: > 100.000; Cover material: Polycarbonate PC; Input voltage span: 220-240 V AC; Warranty in years: 0; Housing material: Aluminium; L/B value: L80/B10; Input voltage range luminaire: 220-240 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; Optics of the cover: frosted; Light colour according to EN 12464-1: neutral white 3300 to 5300 K
width: 66mm