

DOTLUX LED basement light OVAL 4.5W 4000K IP44

Order number: 5380-040120

- Oval surface-mounted LED cellar light for ceiling and wall mounting, particularly suitable for rooms with high humidity such as cellars, underground garages and ducts.
- Impact-resistant frosted glass diffuser made of Makrolon® (BAYER) ensures high light transmission.
- Simple installation thanks to foldable light module which is fixed with just one screw
- Three break-out cable outlets allow flexible cabling
- Suitable for 20 mm plastic electrical conduits or cable grommets
- 2x cable grommets are included in the scope of delivery

Net luminous flux in lumens: 370; Power consumption in watts: 4,5; Lumen per watt: 82; Beam angle: 120°; protection class (IP): IP44; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 35.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,93; Inrush current in A: 0; IK protection: IK10; Lumen per watt: 82; Protection class: II; Voltage type: AC; Housing colour: white; Warranty in years: 5; L80/B10: 25000; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 25000; LED-Lifetime light source L70/B50 at 25°C: 50000; ETIM Gruppen-ID: EC002892; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSL: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK10; Covering of the luminaire with thermally insulating material possible: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 50000; Lifetime L90/B10 at 25°C: 12500; Pulse duration in µs: 0; Lifetime L90/B50 at 25°C: 16667; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: F; Colour of light adjustable: No
width: 85mm