

DOTLUX LED continuous-row system LINEAcompact Blind unit single-length

Order number: 4954

Single-length LINEAcompact blind unit.

protection class (IP): IP54; Light color: -; Input voltage: 176 - 240 V AC/DC; Color temperature in Kelvin: -; Inrush current in A: 0; IK protection: -; Protection class: I; Voltage type: AC/DC; Housing colour: -; Suited for emergency lighting: No; Input voltage span: 176-240 V AC/DC; Suitable for surface mounting: Yes; Suitable for mounting: No; Input voltage range luminaire: 176-240 V AC/DC; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; With illuminant: No; Suitable for wall mounting: No; Suitable for suspended mounting: No; Suitable for ceiling mounting: Yes; Suitable for light line configuration: Yes; Lamp holder: -; Type of grid: -; Type of control gear: -; With control gear: No; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Light distributor: -; Light sharing: -; Beam angle: -; Light outlet: -; Impact strength: -; Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: Yes; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: No; Covering of the luminaire with thermally insulating material possible: No; With air slots: No; Filament test according to IEC 60695-2-11: -; Constant light output (CLO): No; Type of wiring: Through wiring included; Connection type: Push-in clamp; Photobiological safety according to EN 62471: -; Colour of light adjustable: -; Luminous flux adjustable: -; Beam angle adjustable: -; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Exchangeable control gear: No; Lamp type: -; Emergency power supply integrated: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Surface protection housing: Other; Material cover: Without cover width: 66mm