

**DOTLUX LED damp-proof luminaire HIGHFORCE narrow IP66/IP69 1455mm 45W 4000K IK06 1x5-pole DALI**

Order number: 4772-140050

- UV-stable diffuser and housing
- Suitable for outdoor use thanks to integrated pressure compensation valve
- Chemical-resistant special diffuser made of ChemRST material
- Suitable for agricultural applications
- Housing made of impact-resistant polycarbonate
- Impact resistance IK06
- Suitable for central battery
- IP66/ IP69
- D-certified
- DLG certified
- Distance between both mounting brackets adjustable (700-980mm)
- Mounting brackets allow ceiling and/or wall mounting
- Suitable for mounting heights from 6m thanks to narrow beam optics
- All HIGHFORCE luminaires are delivered without connector plug. Accessories can be found here in the store.

Power consumption in watts: 45; Net luminous flux in lumens: 6810; Lumen per watt: 151; Beam angle: 50°; protection class (IP): other IP66 / IP69; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,95; Inrush current in A: 0; IK protection: IK06; Lumen per watt: 151; Protection class: I; Housing colour: gray; Food-Ready: Yes; Warranty in years: 7; Assortment: Highline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Material cover: Plastic matt/satinized; No dim function: No; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK06; Covering of the luminaire with thermally insulating material possible: No; Dimming DALI-2: Yes; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: B; Colour of light adjustable: No  
width: 90mm