

DOTLUX LED damp-proof luminaire SIMPLY IP54 1160mm 27W 4000K IK10

Order number: 4669-140140

- Housing made of shatterproof polycarbonate with frosted cover for shadow-free light distribution
- 3-pole through-wiring with internal luminaire terminal block and two gaskets
- easy-to-maintain modular internal design with highest quality components
- Cable ducts on the back facilitate installation and through-wiring for surface mounting
- Silicone-free
- Sustainable product design due to easily replaceable components

Net luminous flux in lumens: 3650; Lumen per watt: 135; Power consumption in watts: 27; Beam angle: 140°; protection class (IP): IP54; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,95; Inrush current in A: 0; IK protection: IK10; Lumen per watt: 135; Protection class: I; Housing colour: white; Suited for emergency lighting: yes; Switch cycles: > 100.000; Warranty in years: 5; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK10; Suitable for emergency lighting: Yes; Covering of the luminaire with thermally insulating material possible: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Colour of light adjustable: No
width: 109mm