

**DOTLUX LED downlight CIRCLEmini 2700K 3W - Very low installation depth -**

Order number: 2775

- Perfect for renovations due to the low installation depth and large cover
- Driver and module can be replaced individually with lockable quick-connect system
- Maintenance-friendly, modular system components
- Natural color perception thanks to extra high CRI value > 92

Power consumption in watts: 3; Net luminous flux in lumens: 280; Lumen per watt: 93; Beam angle: 38°; protection class (IP): IP20; Light color: white; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 2700; Color-rendering-index: CRI > 92; Inrush current in A: 0; Lumen per watt: 93; Housing colour: white; Suited for emergency lighting: yes; Switch cycles: > 100.000; Installation opening diameter in mm: 55-68; Warranty in years: 3; L80/B10: 50000; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 100000; ETIM Gruppen-ID: EC001744; Material cover: Glass transparent; Dimming depending on control gear: Yes; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Suitable for emergency lighting: Yes; Lifetime L70/B50 at 25°C: 100000; Lifetime L90/B10 at 25°C: 25000; Pulse duration in µs: 0; Lifetime L90/B50 at 25°C: 35000; BEG funding: Only relevant in Germany; Dreh- /Schwenkbar: not swivelling; Energieeffizienzklasse der Lichtquelle einer Leuchte: F; Colour of light adjustable: No; Adjustability: Not adjustable  
diameter: 75mm