

DOTLUX LED downlight UNISIZEplus 12W COLORselect

Order number: 4446-0FW120

- Dimmable surface-mounted light for all installation openings from 60-130mm (phase cut-off)
- Easy installation thanks to removable, infinitely adjustable mounting bracket with safety catch/mounting aid
- Removable spring clips allow direct screwing to walls and ceilings
- Extremely space-saving design thanks to integrated ballast
- Stable light output thanks to non-yellowing PMMA light guide
- Decorative rings in 3 colors with magnetic attachment optionally available
- Can also be integrated into DALI networks via optional DALI trailing edge phase dimmer
- COLORselect: 3 light colors in one luminaire. The right light color for every application:

- Warm white 3,000K: Hotel, store, wellness/spa areas, home & living
- Neutral white 4,000K: Office, catering, sanitary facilities, retirement homes and hospitals
- Daylight white 5,700K: conference rooms, educational facilities, office

Power consumption in watts: 12; Net luminous flux in lumens: 960; Lumen per watt: 80; Beam angle: 120°; protection class (IP): IP20; Light color: multicoloured; Input voltage: 220 - 240 V AC; Service life: approx. 35.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; IK protection: IK05; Lumen per watt: 80; Protection class: II; Voltage type: AC; Housing colour: white; Suited for emergency lighting: No; Glare-free: UGR < 25; Switch cycles: > 70.000; Installation opening width in mm: 0; Installation opening diameter in mm: 60-130; Installation opening length in mm: 0; Input voltage span: 220-240; Warranty in years: 3; L80/B10: 35000; Rated current: 0.05; Suitable for surface mounting: Yes; Suitable for mounting: Yes; Dimming without dimmer: No; Input voltage range luminaire: 220-240; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 35000; LED-Lifetime light source L70/B50 at 25°C: 70000; Lifetime L80/B20 at 25°C: 0; ETIM Gruppen-ID: EC001744; With illuminant: Yes; Suitable for wall mounting: No; Suitable for suspended mounting: No; Suitable for ceiling mounting: Yes; Suitable for workplace according to EN 12464-1: No; Suitable for number of light sources: 1; Lamp holder: other Without; Material cover: Plastic, structured; Type of control gear: LED operating device current-controlled; With control gear: Yes; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: Yes; Dimming phase cut-off: Yes; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Light distributor: Diffuser lens/optic/panel; Colour consistency (McAdam ellipse): SDCM6; Degree of protection (NEMA): 1; Impact strength: IK05; Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: No; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: Yes; Covering of the luminaire with thermally insulating material possible: No; Filament test according to IEC 60695-2-11: 650 °C - 30 s; Constant light output (CLO): No; Type of wiring: Through wiring included; Connection type: Cable; Photobiological safety according to EN 62471: RG0; Colour of light adjustable: Positions; Luminous flux adjustable: Positions; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Suitable for low voltage cable system: No; Suitable for clamp-mounting: No; Suitable for light-track mounting: Yes; Suitable for pedestal/floor mounting: No; Suitable for traverse mounting: No; Exchangeable control gear: No; Suitable for lamp power in w: 10; Lamp type: LED not exchangeable; Emergency power supply integrated: No; Surface brushed: No; Dimming DALI-2: No; Dimming phase cut-on: Yes; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 70000; Lifetime L90/B10 at 25°C: 17500; Pulse duration in µs: 0; Lifetime L90/B50 at 25°C: 25000; BEG funding: Only relevant in Germany; LED-Betriebsstrom in mA: 70; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Beam angle adjustable: No; Reflector: White; Light sharing: Symmetric; Light outlet: Direct/indirect; Adjustability: Not adjustable; Beam angle: Extreme wide beam >80°; Surface protection: Untreated diameter: 164mm