

DOTLUX LED high bay spotlight COOLER 100W 5000K 60° beam angle

Order number: 5260-050060

- Suitable for high temperature environments up to 70°C.
- Cold forged heat sink with 2 times higher thermal conductivity than die cast provides optimal heat dissipation.
- Vertical cooling fins prevent dust buildup and provide durable cooling
- Extremely robust and durable ESG real glass cover also resists oil and cleaning agents
- Pressure equalization valve extends seal life and prevents condensation inside the luminaire
- Modular design for different power spectrums
- Glare reduced UGR<19 for 60° version

Power consumption in watts: 100; Net luminous flux in lumens: 15300; Lumen per watt: 153; Beam angle: 60°; protection class (IP): IP66; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: ; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 82; IK protection: IK08; Lumen per watt: 153; Protection class: I; Voltage type: AC; Housing colour: black; Switch cycles: > 40.000; Overvoltage protection: up to 10000 V; Warranty in years: 5; Assortment: Highline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO01744; Material cover: Glass transparent; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK08; Covering of the luminaire with thermally insulating material possible: No; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Colour of light adjustable: No
diameter: 220mm