

**DOTLUX LED high bay spotlight LIGHTSHOWERclean 150W 5000K DALI dimmable**

Order number: 4869-050090-B-Ware

- optimized light distribution due to glare-reduced lens optics and additional glare control on the housing side
- cooling finless design due to extra large die-cast aluminum housing for perfect thermal management
- suitable for use in food processing plants (HACCP)
- cover made of impact-resistant, shatterproof polycarbonate IK10
- protected against strong water jets and high pressure/steam jet cleaning (IP66/IP69)
- sustainable, repairable product design

Lumen per watt: 140; Power consumption in watts: 150; Net luminous flux in lumens: 21000; Beam angle: 90°; protection class (IP): other IP66 / IP69; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 82; Power Factor: 0,92; Inrush current in A: 0; IK protection: IK10; Lumen per watt: 140; Protection class: I; Housing colour: white; Switch cycles: > 100.000; Food-Ready: Yes; Overvoltage protection: up to 6000 V; Input voltage span: 100-240 V AC; Warranty in years: 0; Input voltage range luminaire: 100-240 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC001744; Dimming DALI: Yes; Impact strength: IK10; Pulse duration in µs: 0