

DOTLUX LED house number light WALLsquare 24cm 6W 3000K with dimmer switch (can be deactivated)

Order number: 5046-130120

- High-quality aluminum housing with powder coating in RAL7016
- Robust, water-jet protected design for outdoor use with IP 65 protection
- Glare-free, homogeneous and shadow-free light distribution
- EasyBase platform enables simple and fast installation
- with twilight switch
- Mounting accessories included
- Insect-friendly illumination due to warm white LED'
- Order separately the house number set 4751:
 - This includes 3 sets of numbers (0 - 9) and one set of letters each in upper case (A - H) and lower case (a - h) with a letter height of 8.5 cm.

Power consumption in watts: 2,5; Net luminous flux in lumens: 400; Lumen per watt: 160; Beam angle: 120°; protection class (IP): IP65; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 30.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 160; Voltage type: AC; Housing colour: black; Suited for emergency lighting: No; Warranty in years: 5; Suitable for surface mounting: Yes; Suitable for mounting: No; ENABLED licensed product: Yes; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; With illuminant: Yes; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: Yes; Suitable for light line configuration: No; Suitable for workplace according to EN 12464-1: No; With control gear: No; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Light distributor: Diffuser lens/optic/panel; Colour consistency (McAdam ellipse): SDCM5; Degree of protection (NEMA): 3; Impact strength: IK08; Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: Yes; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: Yes; Covering of the luminaire with thermally insulating material possible: No; Connection type: -; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Exchangeable control gear: No; Suitable for lamp power in w: 2,5; Lamp type: LED not exchangeable; Emergency power supply integrated: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Light outlet: Direct; Colour of light adjustable: No; Luminous flux adjustable: No; Beam angle adjustable: No; Type of grid: Matt; Light sharing: Symmetric; Surface protection housing: Powder coating; Beam angle: Extreme wide beam >80°; Type of control gear: Not required width: 235mm