

DOTLUX LED light MOONBASE 18W 3000K

Order number: 3901-030360

- Acrylic glass ring with micro print sets attractive light effects
- Removable front cover allows easy mounting on ceiling and wall
- Separately available cover caps offer the possibility of individualization
- Suitable for central battery

Power consumption in watts: 18; Consumption (kWh/1000h): 18; Net luminous flux in lumens: 1690; Lumen per watt: 94; Beam angle: 360°; protection class (IP): IP40; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Power supply: Internal; Color-rendering-index: CRI > 82; Inrush current in A: 0; IK protection: IK05; Lumen per watt: 94; Protection class: I; Voltage type: AC/DC; Housing colour: white; Suited for emergency lighting: yes; Glare-free: UGR < 25; Switch cycles: > 100.000; Cover material: PMMA; Input voltage span: 100-277 V AC; Warranty in years: 7; Housing material: Aluminium; L/B value: L80/B10; Suited for emergency power: -; Input voltage range luminaire: 100-277 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK05; Suitable for emergency lighting: Yes; Exchangeable control gear: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; Optics of the cover: clear
diameter: 370mm