

DOTLUX LED light MOONBASE 18W 3000K

Order number: 3901-030360-B-Ware

Acrylic glass ring with microprint creates attractive lighting effects
Removable front cover enables easy mounting on ceiling and wall
Separately available cover caps offer the option of individualization
Suitable for central battery

Power consumption in watts: 18; Net luminous flux in lumens: 1690; Beam angle: 360°; protection class (IP): IP40; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; IK protection: IK05; Protection class: I; Voltage type: AC/DC; Housing colour: white; Glare-free: UGR < 25; Switch cycles: > 100.000; Input voltage span: 100-277 V AC; Warranty in years: 0; Input voltage range luminaire: 100-277 V AC; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK05; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No
diameter: 370mm