

DOTLUX LED light band system LINEAcompact 50W narrow beam 1452mm 5000K not dimmable

Order number: 4945-050045

- All units are delivered fully assembled and only need to be plugged together
- Flexible phase selection directly at the luminaire
- Patent-protected LED cover ensures error-free assembly
- High-quality aluminum core board guarantees perfect cooling and a long service life of the LM80 certified LEDs
- Future-proof with replaceable LED module and separate driver

Power consumption in watts: 50; Net luminous flux in lumens: 8500; Beam angle: 45°; protection class (IP): IP54; Input voltage: 176 - 240 V AC/DC; Service life: ; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 82; Power Factor: 0,98; Protection class: I; Voltage type: AC; Switch cycles: > 200.000; L80/B10: 100000; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 100000; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No
width: 66mm