

DOTLUX LED luminaire CIRCLEugr-top 25W 3000/4000/5700K COLORselect black

Order number: 4366-0FW090

- Adjustable power: 15W, 20W or 25W selectable
- Ideal for office workplaces, as UGR value <19
- Tool-free terminal connection (through-wirable with integrated strain relief)
- Splash-proof housing design (IP 54 front)
- Suitable for central battery
- \"COLORselect\": 3 light colors in one luminaire. The right light color can be set for every application environment.
 1. Warm white 3,000 K: Hotel, store, wellness/spa areas, home & living
 2. Neutral white 4,000 K: Office, gastronomy, industry, sanitary, retirement homes and hospitals
 3. Daylight white 5,700 K: Industry, conference rooms, educational institutions, office

Power consumption in watts: 15/20/25; Net luminous flux in lumens: 2890; Lumen per watt: 116; Beam angle: 90°; protection class (IP): IP54; Light color: multicoloured; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; Lumen per watt: 116; Protection class: I; Voltage type: AC/DC; Housing colour: black; Glare-free: UGR < 19; Warranty in years: 5; L80/B10: 50000; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 60000; ETIM Gruppen-ID: EC001744; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Colour of light adjustable: Positions; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 60000; Lifetime L90/B10 at 25°C: 15000; Pulse duration in µs: 0; Lifetime L90/B50 at 25°C: 20000; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Material cover: Without cover
diameter: 210mm