

DOTLUX LED luminaire MULTIsun 8W 2000-2800K Sunset dimming (without decorative screen)

Order number: 3422

- Flexible: Design your luminaire yourself and order luminaire and bezel separately according to your desired combination
- Screwless installation: Strain relief and connection terminal on the enclosed ballast via push-clamp technology - Multiple MULTIsun can be wired through
- SUNSETdimming for atmospheric and cozy lighting design
- Including phase dimming/ dimmable power supply unit (130 x 25 x 45 mm)
- This luminaire can be upgraded for use as emergency lighting.
(The battery kit accessories are required)

Power consumption in watts: 8; Net luminous flux in lumens: 500; Lumen per watt: 63; Beam angle: 38°; protection class (IP): IP65; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 40.000 h at 25°C; Color temperature in Kelvin: 2000-2800; Color-rendering-index: CRI > 82; Inrush current in A: 0; Lumen per watt: 63; Protection class: III; Housing colour: black; Switch cycles: > 80.000; Installation opening diameter in mm: 68; Input voltage span: 220-240 V AC; Warranty in years: 7; Input voltage range luminaire: 220-240 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO01744; Material cover: Glass transparent; Dimming mains voltage modulation: Yes; Dimming phase cut-off: Yes; No dim function: No; Colour consistency (McAdam ellipse): SDCM6; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Exchangeable control gear: No; Emergency power supply integrated: No; Dimming phase cut-on: Yes; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; LED-Betriebsstrom in mA: 350; Energieeffizienzklasse der Lichtquelle einer Leuchte: G; Beam angle adjustable: No; Colour of light adjustable: Continuously variable diameter: 80mm