

DOTLUX LED luminaire insert LINEAlock 1437mm 25-75W 4000K dimmable 1-10V 90°*110° with emergency lighting module

Order number: 5061-040090-NOT-B-Ware

- Glare-reduced 90° PMMA lens optics UGR<21 (2.5-12m light point height)
- Extremely quick mounting thanks to adjustable spring clips
- Environmentally friendly continued use of your existing trunking system
- Independent, integrated cable system (8 x 1.5 mm² incl. emergency lighting charging current) with quick connectors
- Flexible phase selection and power adjustment directly in the luminaire
- Long service life thanks to oversized cooling
- Incl. two safety ropes/mounting aid
- Incl. emergency lighting module with lithium ion battery 3h 1200Lm

Adjustable output with POWERselect:

- 13550lm@ 75W
- 11850lm@ 65W
- 10200lm@ 55W
- 8650lm@ 45W
- 7850lm@ 40W
- 6750lm@ 35W
- 5850lm@ 30W
- 4800lm@ 25W

Power consumption in watts: 25-75; Net luminous flux in lumens: 13550; Lumen per watt: 196-180; Beam angle: 90° x 110°; protection class (IP): IP40; Light color: white; Input voltage: 186 - 240 AC/DC; Service life: ; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 83; Power Factor: 0.95; Inrush current in A: 0; IK protection: IK06; Battery runtime: 3h; Lumen per watt: 196-180; Housing colour: white; Switch cycles: > 100.000; Warranty in years: 0; L80/B10: 100000; Power emergency operation in W: 6.5; Assortment: Proline; Lifetime L80/B10 at 25°C: 100000; LED-Lifetime light source L70/B50 at 25°C: 200000; Dimming 1-10 V: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK06; Lifetime L70/B50 at 25°C: 200000; Lifetime L90/B10 at 25°C: 50000; Pulse duration in µs: 0; Lifetime L90/B50 at 25°C: 0; BEG funding: only relevant in Germany; Colour of light adjustable: No width: 67mm