

DOTLUX LED moisture-proof luminaire MISTRALht High-Temp IP66 1524mm 65W 4000K-B-Goods

Order number: 4606-040120-B-Ware

- UV-stable housing and impact-resistant safety glass
- Aluminum housing
- IK10 impact resistance
- Stainless steel fasteners
- Suitable for central battery
- Suitable for use at high temperatures

Power consumption in watts: 65; Net luminous flux in lumens: 8100; Lumen per watt: 125; Beam angle: 120°; protection class (IP): IP66; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000h at 65°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; Lumen per watt: 125; Protection class: I; Warranty in years: 0; Ammoniac resistance: Yes; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Housing colour: silver
width: 105mm