

**DOTLUX LED panel FLATeco 620x620 max. 40W 4000K UGR<19**

Order number: 3616-340120-B-Ware

- LED recessed luminaire with microprismatic cover CDP Nano
- Excellent price-performance ratio
- Glare-free, homogeneous and shadow-free light distribution
- Fatigue-free working thanks to flicker-free light
- Better contrast rendition with very good colour rendition and constant colour temperature
- White frame and connection cable with plug connector
- LM80 certified LEDs

**Power levels:**

40W @ 1050 mA

36W @ 950 mA

27W @ 700 mA

20W @ 500 mA

14W @ 350 mA

This product is not compatible with our mounting frame 2039.

Power consumption in watts: max. 40; Net luminous flux in lumens: max. 4000; Lumen per watt: 100; Beam angle: 120°; protection class (IP): IP20; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Inrush current in A: 0; IK protection: ; Lumen per watt: 100; Protection class: III; Housing colour: white; Glare-free: UGR < 19; Switch cycles: > 100.000; Warranty in years: 0; Assortment: Ecoline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Impact strength: IK02; Pulse duration in µs: 0; Surface protection housing: Powder coating width: 620mm