

DOTLUX LED pendant light SLIM 30 3W 3000K

Order number: 2419

- Indirect ceiling lighting with an OSRAM® LED
- The CITIZEN® LED with 3-step MacAdam color sorting guarantees consistent light color even with repeat orders
- Passive die-cast aluminum heat sink
- Powder-coated aluminum housing
- Incl. white canopy and cable suspension (150 cm)

Power consumption in watts: 32; Net luminous flux in lumens: 2340; Lumen per watt: 71; Beam angle: 40°; protection class (IP): IP20; Temperature range: -40°C to +40°C; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 85; Inrush current in A: 0; Lumen per watt: 71; Housing colour: white; Switch cycles: > 100.000; Input voltage span: 100-240 V AC; Warranty in years: 5; Rope length: 1500; similar to RAL-Colour: 9003; Input voltage range luminaire: 100-240 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO01743; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Colour of light adjustable: No; Material cover: Without cover diameter: 100mm