

**DOTLUX LED power supply QUICK-FIXadapt CC 400-700mA**

Order number: 4936-1

Non-dimmable power supply unit for QUICK-FIXadapt with 500mA and IP40.

- incl. magnetic attachment
- Input voltage: 220-240 V AC
- Output voltage: 27 - 42 V DC
- The temperature range at which the power supply unit can be used is between -20°C and 40°C.
- The cable length of the power supply unit is 24cm.

Power consumption in watts: 20; protection class (IP): IP20; Input voltage: 186 - 240 AC/DC; Output current in A: 0,5; Power Factor: 0,97; Inrush current in A: 0; Tc temperature in °C: 85; Protection class: II; Suited for emergency lighting: yes; Output voltage: 25 - 40 DC; Warranty in years: 5; Dimming without dimmer: No; ETIM Gruppen-ID: EC002710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: Yes; Suitable for emergency lighting: Yes; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany  
width: 48mm