

DOTLUX LED rescue light EXIT 3,8W 6000K incl. 4 pictograms 3h operation,(continuous operation or emergency lighting) Li-FEPO4 autom. self test

Order number: 5389

- \"ONE FOR ALL\" One order number for all arrow directions.
- Splash-proof housing (IP65) made of shatterproof polycarbonate
- Replaceable LiFePO4 battery guarantees a light duration of 3 hours
- Different switching programs selectable: continuous or stand-by switching
- Integrated control LED for operating status
- Power consumption in standby mode less than 0.5 Watt
- Automatic self-test function
- Including 4 self-adhesive standard pictograms (left ,right, top, bottom)

Power consumption in watts: 3,8; Net luminous flux in lumens: AC 380 / Akku 240; Lumen per watt: 100; Beam angle: 120°; protection class (IP): IP65; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Output Lumen during emergency: 220; Range of sensor: 20; Color temperature in Kelvin: 6000-7000; Color-rendering-index: CRI > 70; Power Factor: 0,45; IK protection: IK08; Battery runtime: 3h; Lumen per watt: 100; Protection class: I; Voltage type: AC/DC; Housing colour: white; Pictogram included: Yes; L80/B10: 50000; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 100000; ETIM Gruppen-ID: ECD01957; With illuminant: Yes; Impact strength: IK08; Constant light output (CLO): Yes; Mounting method: Ceiling mounting; With remote control: No; Lifetime L70/B50 at 25°C: 100000; Lifetime L90/B10 at 25°C: 25000; Lifetime L90/B50 at 25°C: 33333; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Material cover: Other
width: 107mm