

**DOTLUX LED rescue light EXITflat with self-test 3W 6000K incl. 4 pictograms**

Order number: 5406

- For wall mounting with LED light surface on one side
- Replaceable rechargeable battery (LiFePO4) with a lighting duration of 3 hours
- Different switching programs selectable: continuous or standby switching
- Power consumption in standby mode less than 0.5 Watt
- Automatic self-test function with integrated operating status control LED
- Including standard pictograms (left, right, up, down)
- The luminaire has integrated escape route lighting

Power consumption in watts: 3; Net luminous flux in lumens: AC 38 / Akku 29; Lumen per watt: 13; Beam angle: 180°; protection class (IP): IP20; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Range of sensor: 30; Color temperature in Kelvin: 6000; Color-rendering-index: CRI > 70; Power Factor: 0,5; Lumen per watt: 13; Protection class: I; Housing colour: multicoloured; Input voltage span: 220-240 V AC; Warranty in years: 3; L80/B10: 50000; Input voltage range luminaire: 220-240 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 100000; ETIM Gruppen-ID: EC001957; Lifetime L70/B50 at 25°C: 100000; Lifetime L90/B10 at 25°C: 25000; Lifetime L90/B50 at 25°C: 33333; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Material cover: Other width: 187mm