

DOTLUX LED safety light EXITtop with self-test incl. 2 interchangeable lenses white 3h

Order number: 3679-1

- Universally mountable safety light for recessed and surface mounting
- Replaceable rechargeable battery with a lighting duration of 3 hours
- Integrated pushbutton and control LED for operating status display
- Only suitable for stand-by mode. If the light is supplied with mains power, the integrated rechargeable battery charges and the light is in stand-by mode.
- Incl. two easy to change lenses
 - Corridor lighting (asymmetric)
 - Wide beam
- Automatic self-test function

Power consumption in watts: 0,5; Net luminous flux in lumens: 240; Beam angle: 180°; protection class (IP): IP20; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 5000; Power Factor: 0,25; Battery runtime: 3h; Protection class: II; Housing colour: white; Installation opening diameter in mm: 120; Input voltage span: 220-240 V AC; Warranty in years: 3; Input voltage range luminaire: 220-240 V AC; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC001957; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Material cover: Other diameter: 140mm