

**DOTLUX LED solar bollard light FLASHground with sensor 100 cm 3.5W 3000K**

Order number: 4966-030120

- Solar lithium-ion battery light with motion sensor (2 selectable modes)
- Reliable and fast battery charging due to large SOLAR panel, also suitable for indirect light incidence
- Particularly insect-friendly lighting due to warm white LEDs and motion sensor
- High-quality, splash-proof aluminum housing with weather-resistant powder coating
- Large homogeneously designed light area enables glare-free light distribution
- Includes rechargeable battery (replaceable) and mounting accessories
- Concrete anchor optionally available Article no.: 4968

Operating modes Motion sensor:

A) 15% permanent light intensity after sunset , 100% light intensity when motion (duration 15 seconds).

B) 0% light intensity after sunset, 100% light intensity in case of movement (duration 15 seconds)

Power consumption in watts: 3,5; Net luminous flux in lumens: 250; Lumen per watt: 71; Beam angle: 120°; protection class (IP): IP54; Light color: white; Service life: approx. 30.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Inrush current in A: 0; IK protection: IK06; Battery runtime: 3h at 100% / 20h at 15%; Lumen per watt: 71; Protection class: III; Housing colour: gray; Warranty in years: 3; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC000062; Material cover: Plastic matt/satinized; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK06; Lamp type: LED; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -  
width: 220mm