

DOTLUX LED solar wall light FLASHwall with sensor 3.5W 3000K

Order number: 4965-030120-B-Ware

- Solar lithium-ion battery light with motion sensor (2 selectable operating modes).
- Reliable and fast battery charging due to large SOLAR panel, also suitable for indirect light incidence
- Particularly insect-friendly lighting thanks to warm white LEDs and motion sensor
- High-quality, splash-proof aluminium housing with weather-resistant powder coating
- Large homogeneously designed illuminated surface enables glare-free light distribution
- Easy alignment of the luminaire thanks to adjustable stainless steel mounting bracket
- Includes rechargeable battery (replaceable) and mounting accessories

Operating modes Motion sensor:

A) 15% permanent light intensity after sunset , 100% light intensity in case of movement (duration 15 seconds)

B) 0% light intensity after sunset, 100% light intensity on movement (duration 15 seconds)

Power consumption in watts: 3,5; Net luminous flux in lumens: 250; Beam angle: 120°; protection class (IP): IP54; Service life: approx. 30.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Motion sensor: Infrared, 6-10m, 120°; Inrush current in A: 0; IK protection: IK06; Battery runtime: 3h at 100% / 20h at 15%; Protection class: III; Housing colour: gray; Warranty in years: 0; Capacity of battery in mAh: 1500; Assortment: Proline; ETIM Gruppen-ID: EC002892; Impact strength: IK06; Pulse duration in µs: 0 width: 180mm