

DOTLUX LED spotlight FLOORslim 50W 3000K

Order number: 3198-030120

- Waterproof, reinforced IP 65 housing with efficient cooling design
- ESG safety glass - ULTRA CLEAR - highly transparent glass for excellent light color and improved light output
- Robust, thick-walled die-cast aluminum housing with multiple screws
- Mounting bracket freely rotatable (320°)
- Incl. 1 m connection cable (open ends H05RN-F)
- Suitable for central battery

Power consumption in watts: 50; Net luminous flux in lumens: 5100; Lumen per watt: 102; Beam angle: 120°; protection class (IP): IP65; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: approx. 35.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 80; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 102; Protection class: I; Voltage type: AC; Housing colour: white; Glare-free: UGR < 25; Switch cycles: > 70.000; Overvoltage protection: up to 4000 V; Input voltage span: 100-240 V AC; Warranty in years: 2; Input voltage range luminaire: 100-240 V AC; Assortment: Ecoline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: E0001744; Material cover: Glass transparent; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK08; Covering of the luminaire with thermally insulating material possible: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Dreh- /Schwenkbar: Mounting bracket freely rotatable 320°; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Colour of light adjustable: No; Adjustability: Swivelling width: 210mm