

**DOTLUX LED street light BELUGAmini 73W 4000K SKI without pole mount B-goods**

Order number: 3283-040135-B-Ware

- Protection class I with separate overvoltage protection (10,000 V)
- Variety of adapters enables mounting on all pole diameters
- The multilayer lens optics with CREE® LEDs enable uniform light distribution
- Solid cast aluminum housing in RAL 7022 with impact resistance class IK09 and smooth surface
- Highly efficient PHILIPS® LED driver ensures low maintenance costs
- Future-oriented module design with innovative cooling system
- Easy installation and tool-free maintenance
- Integrated pressure equalization valve

Net luminous flux in lumens: 8760; Power consumption in watts: max. 73; Lumen per watt: 120; Beam angle: 135°/50°; protection class (IP): IP66; Input voltage: 176 - 240 V AC/DC; Service life: approx. 80.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 80; Mast support: depending on adapter; Lumen per watt: 120; Protection class: I; Housing colour: gray; Switch cycles: > 160.000; Overvoltage protection: up to 10000 V; Input voltage span: 90-264 V AC; Warranty in years: 0; Input voltage range luminaire: 90-264 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC0000062; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: Yes; Dimming phase cut-on: No; Dimming GPRS: No