

DOTLUX LED surface-mounted light SURFACEdali Ø300x62 22W 3000/4000/5700K COLORselect white

Order number: 4930-199120

- DALI dimmable version
- Quick and easy installation with EASYbase base plate and twistlock fastener
- Wide range of products enables use in all projects (e.g. sensor, exit, DALI ...)
- Sustainable product design thanks to easily replaceable LED module and power supply unit
- Rear and side cable entry with large cable storage space enables flexible use on site
- Ideal for residential projects thanks to impact-resistant IK10 polycarbonate housing
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor areas
- Individual light color adjustable via COLORselect (light color: 3,000 K / 4,000 K / 5,700 K)
- Suitable for central battery

Power consumption in watts: 22; Net luminous flux in lumens: 2640/2690/2670; Lumen per watt: 120/122/121; Beam angle: 120°; protection class (IP): IP54; Light color: multicoloured; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,9; IK protection: IK10; Lumen per watt: 120/122/121; Protection class: II; Voltage type: AC; Housing colour: white; Warranty in years: 5; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO02892; Material cover: Plastic, structured; Dimming DALI: Yes; No dim function: No; Impact strength: IK10; Covering of the luminaire with thermally insulating material possible: No; Colour of light adjustable: Positions; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Beam angle: Extreme wide beam >80°
diameter: 300mm