

DOTLUX LED surface-mounted light SURFACEsensor-exit Ø300x62 25W 3000/4000/5700K COLORselect white

Order number: 4932-199120

- Additional 3h emergency light function with built-in lithium ion battery
- Version with motion (radar) and daylight sensor (several lights can be programmed with one remote control, please order remote control 5713 separately)
- Quick and easy installation with EASYbase base plate and twistlock fastener
- Wide range of products enables use in all projects (e.g. sensor, exit, DALI ...)
- Sustainable product design thanks to easily replaceable LED module, power supply unit and battery
- Rear and side cable entry with large cable storage space enables flexible use on site
- Ideal for residential projects thanks to impact-resistant IK10 polycarbonate housing
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor areas
- Individual light color adjustable via COLORselect (light color: 3,000 K / 4,000 K / 5,700 K)

Power consumption in watts: 22; Net luminous flux in lumens: 2640/2740/2700; Lumen per watt: 120/124/122; Beam angle: 120°; protection class (IP): IP54; Light color: multicoloured; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,9; IK protection: IK10; Battery runtime: 3h; Lumen per watt: 120/124/122; Protection class: II; Voltage type: AC; Housing colour: white; Suited for emergency lighting: yes; Switch cycles: > 100.000; Warranty in years: 5; L80/B10: 50000; ENABLED licensed product: Yes; Power emergency operation in W: 3; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; ETIM Gruppen-ID: EC002892; Material cover: Plastic, structured; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK10; Suitable for emergency lighting: Yes; Covering of the luminaire with thermally insulating material possible: No; Colour of light adjustable: Positions; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Beam angle: Extreme wide beam >80° diameter: 300mm