

**DOTLUX LED surface mounted luminaire SURFACEdali Ø400x62 30W 3000/4000/5700K COLORselect white**

Order number: 4931-0FW120

- DALI dimmable version
- Quick and easy mounting with EASYbase base plate and twistlock fastener
- Large product variety allows use in all projects ( e.g. sensor, exit, DALI ...)
- Sustainable design, LED module and power supply can be exchanged without tools
- Rear and side cable entry with large cable storage space allow flexible use on site
- Ideal for residential projects due to impact resistant polycarbonate housing IK10
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor use
- Individual light color adjustable by COLORselect (light color: 3,000 K / 4,000 K / 5,700 K)
- Suitable for central battery
- The large luminous surface made of polycarbonate creates a uniform and at the same time ceiling-brightening light distribution
- Flexible cable entry possible at the rear and side

Net luminous flux in lumens: 2850-3000; Power consumption in watts: 30; Lumen per watt: max. 100; Beam angle: 120°; protection class (IP): IP54; Light color: multicoloured; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,97; Inrush current in A: 0; IK protection: IK10; Lumen per watt: max. 100; Protection class: II; Voltage type: AC; Housing colour: white; Warranty in years: 5; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO02892; Material cover: Plastic matt/satinized; Dimming DALI: Yes; No dim function: No; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK10; Covering of the luminaire with thermally insulating material possible: No; Colour of light adjustable: Positions; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: C  
diameter: 400mm