

**DOTLUX LED surface mounted luminaire SURFACEsensor Ø300x62 25W 3000/4000/5700K COLORselect white**

Order number: 4485-1FW120-B-Ware

- Version with motion (radar) and daylight sensor (several luminaires can be programmed with one remote control, please order remote control separately).
- Quick and easy mounting with EASYbase base plate and twistlock fastener
- Large product variety enables use in all projects ( e.g. sensor, Exit, DALI ...)
- Sustainable design, LED module, power supply unit and battery can be replaced without tools
- Rear and side cable entry with large cable storage space allow flexible use on site
- Ideal for residential projects due to impact-resistant polycarbonate housing IK10
- Modern, clear housing with indirect light component
- Splash-proof design for outdoor, wet room and indoor use
- Individual light colour adjustable with COLORselect (light colour: 3,000 K / 4,000 K / 5,700 K)
- Suitable for central battery
- The large luminous surface made of polycarbonate creates a uniform and at the same time ceiling-brightening light distribution
- Flexible cable entry possible at the back and side

Lumen per watt: max.100; Power consumption in watts: 25; Net luminous flux in lumens: 2250-2500; Beam angle: 120°; protection class (IP): IP54; Light color: multicoloured; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,9; IK protection: IK10; Lumen per watt: max.100; Protection class: II; Voltage type: AC; Housing colour: white; Warranty in years: 0; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Impact strength: IK10  
diameter: 300mm