

DOTLUX LED tracklight SLIMtrack-eco 15W 3000K white

Order number: 4890-030036

- EDISON® brand LED and flicker-free power supply unit
- Excellent price-performance ratio
- Natural color perception due to extra high CRI value
- Die-cast aluminum housing
- Passive cooling system without fan

Power consumption in watts: 15; Net luminous flux in lumens: 1500; Lumen per watt: 100; Beam angle: 36°; protection class (IP): IP20; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 35.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 92; Power Factor: 0,9; Inrush current in A: 0; Lumen per watt: 100; Protection class: I; Housing colour: white; Switch cycles: > 70.000; Overvoltage protection: 1500 V; Warranty in years: 3; Assortment: Ecoline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC001744; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: Yes; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Colour consistency (McAdam ellipse): SDCM6; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Dreh-/Schwenkbar: 350° / 90°; Energieeffizienzklasse der Lichtquelle einer Leuchte: E; Colour of light adjustable: No; Adjustability: Rotating and swivelling
diameter: 65mm