

DOTLUX Mirror light TRENDosensor 11W 3000/4000/5700K COLORselect

Order number: 4994-199140

- Modern, stylish design with integrated sensor with user-friendly on/off function
 - Maximum illuminated area without visible screw connections
 - EASYbase platform enables quick and easy installation
 - Mounting on existing drill holes possible thanks to free surface on the base plate
 - 2 cable inlets pre-installed (individual inlets can be drilled into the aluminum base if required)
 - Simply set your desired light color yourself, one article number - three light colors through COLORselect
 - Sustainable product design thanks to easily replaceable components
-
- Sensor with on/off function and daylight detection
 - The following values can be set in stages:
 - Reach range (up to 6m)
 - Daylight sensor
 - Light duration

Power consumption in watts: 11; Net luminous flux in lumens: max. 1200; Lumen per watt: 110; Beam angle: 140°; protection class (IP): IP44; Light color: multicoloured; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,7; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 110; Protection class: I; Housing colour: multicoloured; Switch cycles: > 100.000; Input voltage span: 220-240 V AC; Warranty in years: 5; Input voltage range luminaire: 220-240 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO02892; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK08; Colour of light adjustable: Positions; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: E
width: 85mm