

**DOTLUX QUICK-FIXadapt 29W 3000K interchangeable module**

Order number: 6161-030170

- Universal LED light module for quick and easy replacement of all conventional light sources in ceiling and wall luminaires
- Tool-free replacement of the LED module even by a non-specialist thanks to DC system plug
- Special lenses with 170° beam angle of the LED module also possible by a non-specialist
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- the QUICKFIX-adapt can be set up to 700mA with the matching 5068-1 power supply unit.
- inner diameter 25cm
- outer diameter 30cm
- can be combined with emergency power battery kit art. no. 5315 corresponds to an emergency light output of 1.5 watts at 3H

Power consumption and net luminous flux of the module with different operating currents:

- 12W@ 300mA = 2000lm = 167lm/W
- 14W@ 350mA = 2320lm = 166lm/W
- 16W@ 400mA = 2640lm = 165lm/W
- 18W@ 450mA = 2970lm = 165lm/W
- 23W@ 550mA = 3580lm = 156lm/W
- 25W@ 600mA = 3840lm = 154lm/W
- 27W@ 650mA = 4130lm = 153lm/W
- 29W@ 700mA = 4360lm = 150lm/W

Power consumption in watts: 29; Net luminous flux in lumens: 4360; Lumen per watt: 150; Beam angle: 170°; protection class (IP): IP20; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Lumen per watt: 150; Protection class: -; Voltage type: DC; Switch cycles: > 100.000; Input voltage span: 40-43 DC; Warranty in years: 3; L80/B10: 50000; Dimming without dimmer: No; ENABLED licensed product: Yes; Input voltage range luminaire: 40-43 DC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: D; Lifetime L80/B10 at 25°C: 50000; ETIM Gruppen-ID: EC000996; Colour consistency (McAdam ellipse): SDCM4; Connection type: Cable; Photobiological safety according to EN 62471: RG1; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Flexible: Nein; Suitable for traffic lights: No; External driver required: Yes; Suitable for constant voltage: No; Suitable for general lighting: Yes; Suitable for constant current: Yes; Suitable for rail traffic: No; Suitable for matrix information boards: No; Suitable for variable road signs: No; Light colour according to EN 12464-1: -; BEG funding: only relevant in Germany; LED-Betriebsstrom in mA: 700; Shape: Round; Colour: Yellow  
diameter: 300mm