

DOTLUX Wall lamp BEAMO 10W 3000K white

Order number: 4729-030120

- Rugged, splash-proof design for outdoor use with IP 65 protection
- EasyBase platform allows for simple and quick installation
- Two independently adjustable beam angles with angle indicators allow for uniform lighting effects even on larger projects
- Special light diffuser provides sharp lighting effects with virtually no color distortion
- Particularly insect-friendly lighting thanks to warm white LEDs and asymmetrical light distribution

Power consumption in watts: 10; Net luminous flux in lumens: 900; Lumen per watt: 90; Beam angle: 15° - 120°; protection class (IP): IP65; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; Lumen per watt: 90; Protection class: I; Housing colour: white; Suited for emergency lighting: yes; Switch cycles: > 100.000; Warranty in years: 3; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Material cover: Plastic, transparent; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Suitable for emergency lighting: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Colour of light adjustable: No
width: 97mm