

**DOTLUX Wall light BEAMO 10W 3000K anthracite**

Order number: 5037-130120

- Robust, splash-proof design for outdoor use with IP 65 protection
- EasyBase platform enables quick and easy installation
- Two independently adjustable beam angles with angle indicators
- The special light diffuser enables sharp lighting effects with virtually no color distortion
- Particularly insect-friendly lighting thanks to warm white LEDs and asymmetrical light distribution

Net luminous flux in lumens: 900; Power consumption in watts: 10; Lumen per watt: 90; Beam angle: 15-120°; protection class (IP): IP65; Light color: yellow; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Power Factor: 0,9; IK protection: other; Lumen per watt: 90; Protection class: I; Voltage type: AC; Housing colour: anthracite; Suited for emergency lighting: No; Installation opening width in mm: 0; Installation opening diameter in mm: 0; Installation opening length in mm: 0; Input voltage span: 220-240; Warranty in years: 3; L80/B10: 50000; Suitable for surface mounting: Yes; Suitable for mounting: No; ENABLED licensed product: Yes; Input voltage range luminaire: 220-240; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; ETIM Gruppen-ID: EC002892; With illuminant: Yes; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: No; Suitable for light line configuration: No; Suitable for number of light sources: 0; Material cover: Plastic, transparent; Type of control gear: -; With control gear: Yes; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM2; Degree of protection (NEMA): 4; Impact strength: other; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: No; With air slots: Yes; Filament test according to IEC 60695-2-11: -; Constant light output (CLO): No; Type of wiring: -; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Exchangeable control gear: Yes; Suitable for lamp power in w: 10; Lamp type: LED; Emergency power supply integrated: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Colour of light adjustable: No; Luminous flux adjustable: No; Type of grid: Matt; Light outlet: Direct/indirect; Beam angle adjustable: Continuously variable; Light sharing: Symmetric/asymmetric; Surface protection housing: Powder coating; Light distributor: None; Photobiological safety according to EN 62471: Other; Beam angle: Variable beam angle; Connection type: Other; Lamp holder: Other  
width: 97mm