

DOTLUX Wall light MORPHO 6W 3000K white

Order number: 5918-030120

- Modern, decorative wall light with direct and indirect lighting
- Unique design with great decorative effect
- Robust, splash-proof aluminum housing offers the best protection for outdoor use with IP65 certification
- Excellent heat management thanks to the aluminum housing ensures a long service life

Power consumption in watts: 6; Net luminous flux in lumens: 322; Lumen per watt: 53; Beam angle: 120°; protection class (IP): IP65; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 80; Power Factor: 0,85; Inrush current in A: 0; IK protection: IK05; Lumen per watt: 53; Protection class: I; Voltage type: AC; Housing colour: white; Warranty in years: 3; L80/B10: 55000; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 55000; LED-Lifetime light source L70/B50 at 25°C: 82500; ETIM Gruppen-ID: EC002892; Suitable for wall mounting: Yes; Material cover: Plastic, transparent; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK05; Covering of the luminaire with thermally insulating material possible: No; Filament test according to IEC 60695-2-11: 750 °C - 30 s; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 82500; Lifetime L90/B10 at 25°C: 27500; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: G; Colour of light adjustable: No; Beam angle: Extreme wide beam >80° width: 100mm