

LED power supply CC for QUICK-FIXdc 6-50W 100-1400mA 25-54V DALI dimmable NFC linear Factory setting 350mA/1400mA

Order number: 5047

- DALI-2 certified LED driver, 1-100% dimming range
- SELV output protection for safety and flexibility in luminaires
- Amplitude dimming for highest quality light output, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Suitable for use in emergency lighting applications
- Ideal solution for Class I and Class II

Factory setting of operating current 350mA/1400mA

Power consumption in watts: 6-50; protection class (IP): IP20; Input voltage: 176 - 240 V AC/DC; Output current in A: ; Inrush current in A: 0; Tc temperature in °C: 85; Protection class: II; Overvoltage protection: 1000 V; Output voltage: 25 - 54 DC; Input voltage span: 198-264 V AC / 176-280 V DC; Warranty in years: 5; Dimming without dimmer: No; Input voltage range luminaire: 198-264 V AC / 176-280 V DC; ETIM Gruppen-ID: EC002710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: Yes; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany
width: 30mm