

PRODUCT NO. 4235-050160-NOT

DOTLUX LED trunking system LINEAclick 25W 3W 5000K wide beam with emergency lighting module Made in Germany







to the product page

- Continued use of your existing mounting rail system
- Mounting without mechanical intervention in the mounting rail system with heat-resistant neodymium
 - magnetic brackets incl. safety rope
- Independent, integrated cable system with quick connectors
- Optimized transmittance of the patented LINEAclick lens from DOTLUX®
- Shadow-free light distribution thanks to innovative lens design
- Perfect cooling of the LED module thanks to aluminum core board
- LM80 certified LEDs with 40% current consumption
- Suitable for central battery (only DALI article no. 2814-350045 and 2813-450160)

| | 25 | | 1500 |
|-----------------------------|------|--|-------------------|
| WEIGHT IN KG | 2.5 | BEAM ANGLE | 160° |
| POWER CONSUMPTION IN WATTS | 25+3 | PROTECTION CLASS (IP) | IP40 |
| NET LUMINOUS FLUX IN LUMENS | 4250 | INPUT VOLTAGE | 176 - 240 V AC/DC |
| LUMEN PER WATT | 168 | Service life | |
| | | COLOR TEMPERATURE IN KELVIN | 5000 |
| | | COLOR-RENDERING-INDEX | CRI > 82 |
| | | POWER FACTOR | 0,93 |
| Dimensions | | INRUSH CURRENT IN A | 0 |
| | | LUMEN PER WATT | 168 |
| length: 1530mm | | PROTECTION CLASS | I |
| width: 73mm | | VOLTAGE TYPE | AC |
| height: 61mm | | SWITCH CYCLES | > 200.000 |
| | | WARRANTY IN YEARS | 7 |
| | | L80/B10 | 100000 |
| | | ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| | | LIFETIME L80/B10 AT 25°C | 100000 |
| | | ETIM GRUPPEN-ID | EC002892 |
| | | DIMMING 0-10 V | No |
| | | DIMMING 1-10 V | No |
| | | DIMMING DALI | No |
| | | DIMMING DMX | No |
| | | DIMMING DSI | No |
| | | DIMMING POTENTIOMETER (INTEGRATED) | No |

Page 1/2 Product no.: 4235-050160-NOT DOTLUX LED trunking system LINEAclick 25W 3W 5000K wide beam with emergency lighting module Made in Germany



| DIMMING LINESWITCH | No |
|--|-----|
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | No |
| NO DIM FUNCTION | Yes |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| PULSE DURATION IN μ S | 0 |
| | |