


PRODUCT NO. 5031-040240

## DOTLUX LED floor lamp ROOFbutler 80W 4000K dimmable silver



to the product page

- Aluminum housing in RAL9006 from the series \"ROOF\" with heavy U-steel base.
- Integrated presence sensor activates/dims the luminaire to 30% brightness after 10 minutes and deactivates the luminaire after another 10 minutes
- Glare-free, homogeneous and shadow-free light distribution / smooth top surface
- Better contrast rendition with very good color rendition and constant color temperature (3-Step MacAdam Binning)
- 1.5 m connection cable
- The flicker-free light rendering ensures optimal vision, is easy on the eyes for fatigue-free work and creates a pleasant atmosphere in offices, meeting rooms and hotels.

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120°/120°
<b>WEIGHT IN KG</b>	12.823	<b>LIGHT COLOR</b>	white
<b>POWER CONSUMPTION IN WATTS</b>	80 (direkt: 30 W / indirekt: 50 W)	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>NET LUMINOUS FLUX IN LUMENS</b>	8800	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	4000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,95
<b>Dimensions</b>		<b>INRUSH CURRENT IN A</b>	0
<b>length:</b> 610mm		<b>PROTECTION CLASS</b>	I
<b>width:</b> 310mm		<b>VOLTAGE TYPE</b>	AC/DC
<b>height:</b> 1950mm		<b>GLARE-FREE</b>	UGR < 19
		<b>SWITCH CYCLES</b>	> 100.000
		<b>INPUT VOLTAGE SPAN</b>	220-240 V AC
		<b>WARRANTY IN YEARS</b>	5
		<b>SIMILAR TO RAL-COLOUR</b>	9006
		<b>DIMMING WITHOUT DIMMER</b>	No
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	220-240 V AC
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC000300
		<b>WITH ILLUMINANT</b>	Yes
		<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	Yes
		<b>SUITABLE FOR NUMBER OF LIGHT SOURCES</b>	1
		<b>LAMP HOLDER</b>	-

<b>MATERIAL COVER</b>	Plastic matt/satinized
<b>TYPE OF CONTROL GEAR</b>	LED operating device current-controlled
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	Yes
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	Yes
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	Diffuser lens/optic/panel
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM3
<b>WITH MOVEMENT SENSOR</b>	Yes
<b>WITH LIGHT SENSOR</b>	No
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	Yes
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG1
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>ELECTRICAL CONNECTION WITH CONNECTOR SYSTEM</b>	No
<b>LUMINAIRE HEADS FLEXIBLE</b>	No
<b>DIRECT-/INDIRECT PROPORTION SEPARATELY CONTROLLABLE</b>	No
<b>ADJUSTABLE</b>	Nein
<b>EXCHANGEABLE CONTROL GEAR</b>	Yes
<b>SUITABLE FOR LAMP POWER IN W</b>	-
<b>LAMP TYPE</b>	LED exchangeable
<b>WITH DIMMER</b>	Yes
<b>WITH PRESENCE INDICATOR</b>	No
<b>WITH REFLECTOR</b>	No
<b>WITH SWITCH</b>	No
<b>WITH SEPARATE READING LIGHT</b>	No
<b>MATERIAL</b>	Aluminium
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany

<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	E
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>LIGHT OUTLET</b>	Direct/indirect
<b>LUMINOUS FLUX ADJUSTABLE</b>	Continuously variable
<b>TYPE OF GRID</b>	None
<b>HOUSING COLOUR</b>	silver