

PRODUCT NO. 5037-030120

DOTLUX Wall lamp BEAMO 10W 3000K anthracite



to the product page

- Rugged, splash-proof design for outdoor use with IP 65 protection
- EasyBase platform enables simple and fast installation
- Two independently adjustable beam angles with angle indicators
- Special light diffuser provides sharp lighting effects with virtually no color distortion
- Particularly insect-friendly lighting due to warm white LEDs and asymmetrical light distribution

WEIGHT IN KG	0.49
POWER CONSUMPTION IN WATTS	10
NET LUMINOUS FLUX IN LUMENS	900
LUMEN PER WATT	90

Dimensions

length: 120mm
width: 97mm
height: 100mm

BEAM ANGLE	15° - 120°
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
LUMEN PER WATT	90
PROTECTION CLASS	I
HOUSING COLOUR	anthracite
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	3
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic, transparent
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No

DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
COLOUR OF LIGHT ADJUSTABLE	No