

PRODUCT NO. 5039

DOTLUX LED power supply ZIGBEE 3.0 3-38Watt 300-1050mA 10-54V dimmable



to the product page

P out W	I out DC	I out DC
16	50 : 54	300 mA COPI
18.5	50 : 54	350 mA COPI
21.5	50 : 54	400 mA COPI
24	50 : 54	450 mA COPI
27	50 : 54	500 mA COPI
29.5	50 : 54	550 mA COPI
32	50 : 54	600 mA COPI
35	50 : 54	650 mA COPI
36	50 : 51	700 mA COPI
38	50 : 50	750 mA COPI
38	50 : 47	800 mA COPI
38	50 : 44	850 mA COPI
38	50 : 42	900 mA COPI
38	50 : 40	950 mA COPI
38	50 : 38	1 A COPI
38	50 : 36	1.05 A COPI

- The flicker-free power supply is dimmable via ZIGBEE.
- With constant current technology (CC) it is suitable for constant current luminaires
- The connected constant current luminaires can be dimmed between 1%-100%
- The output current is adjustable:
 - 350/400/450/500/550/600/650/700/750/800/850/900/950/1000/1050mA
- To integrate with Philips Hue Bridge, start the search for new lights in the Hue app and turn on the driver only after the search has started
- MADE in EU

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
		INPUT VOLTAGE	220 - 240 V AC
		Output current in A	
WEIGHT IN KG	0.347	POWER FACTOR	0,95
POWER CONSUMPTION IN WATTS	3-38	INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	80
		PROTECTION CLASS	II
Dimensions		OUTPUT VOLTAGE	10 - 54 DC
		INPUT VOLTAGE SPAN	198-264 V AC
length: 147mm		INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC
width: 44mm		ETIM GRUPPEN-ID	EC002710
height: 30mm		DIMMING ZIGBEE	Yes
		DIMMING WITH PUSH-BUTTON	Yes
		NO DIM FUNCTION	No
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		IFTTT SUPPORT AVAILABLE	No
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany